

VESSEL SPECIFICATIONS

“MARY-V”



“Success through safe diving”

Name;	“MARY-V”	Deck Area;	12m x 6m = 72m²
AMSA UVI;	438630	Deck Crane;	Sea Crane 121-3 (1000kgs@12m, & 5000kgs@2.45m)
Call Sign;	VNW 6029	Hyd Winch (2);	2t Single Drum (& Capstan)
DOT Survey;	2B (200Nm 4 +8)	Anchor Winch (2);	10t Single Drum
OVID Report;	FQNJ-2394-9511-6822 (Insp: 28/04/23)	Hyd Oil;	280ltrs
LOA;	19mtrs	Comp Air;	40 cu ft/min@10bar (Diving grade air)
Beam;	6.3mtrs	Desalination;	Citor (100ltr/hr)
GWT;	45 tonnes	Fresh Water;	1000ltr storage tank
Hull;	Aluminium Catamaran	Hot Water;	80ltrs (240V)
Accom;	4 persons	Sullage;	180ltr Storage – (Class A)
Propulsion;	2 x Yanmar 6CXM- GTYE (360hp each)	Galley;	Microwave, T.V, Dinette, Fridge, Freezer
Cruise Speed;	10 kts		
Max Speed;	14kts		
Range;	750Nm (Cruise)		
Fuel;	7000ltrs		
Consumption;	80ltr/hr – Cruise speed		
Auxiliary;	IS16S (16kva) & IS 34S (34 kva)		
Deck Cargo;	14t (Max)		



OCEANIC OFFSHORE PTY LTD
Commercial Diving Services

Tel;
Email;
Website:

(08) 9183 6777
oceanic@oceanicoffshore.com.au
www.oceanicoffshore.com.au